## Codan 3304 Air / Water Hose



🕰 CODAN 3304 AIR AND WATER HOSE - WP 25 BAR

## Codan 3304 - ISO 1403: 1995

Extremely flexible, grey universal hose. Suitable for cold and hot water, compressed air and certain chemicals. Resistant to acetates and ketones. The outer rubber coating ensures excellent resistance to ozone. For air and water where there are high demands on quality.

Please contact Codan for further information.

Type nr. 3304 Application: Air / Water Hose Standard Length: 50 metres Working Temperature: -40°C to 100°C Inside: EPDM Colour: Black Reinforcement: Ester Outside: EPDM Colour: Grev Standards: ISO 1403: 1995

Inside dia. (mm)	Outside dia. (mm)	Working Pressure BAR	Burst Pressure BAR	Bend Radius (mm)	Weight (g/m)	Product code
6,3	14,3	25	80	50	179	3304006000
7,9	15,9	25	80	60	207	3304008000
9,5	17,5	25	80	65	236	3304010000
12,7	21,5	25	80	75	330	3304013000
15,9	24,7	25	80	90	397	3304016000
19,1	29,5	25	70	105	560	3304019000
25,4	36,2	20	50	130	724	3304025000
32,0	41,7	10	40	150	766	3304032000
38,1	48,0	10	40	170	898	3304038000

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. Written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care and inspection of hoses before use. Hosesshould be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage

of vulcanised Rubber Products). The individual conditions of an application will affect the life time of each product. Therefore of VUC4heet nuover Producty). The invariant consists of an appendix the invariant of the product information is completed with. Codan please ensure that resistance to chemicals and cleaning procedures in our written product information is completed with. Codan Rubber's warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification. Please contact Codan Rubber for individual product manufacturing tolerances.



© Codan Rubber Danmark A/S Valdemarshaab 1, DK-4600 Køge, Denmark Tel. +45 56 64 64 64 Fax +45 56 64 65 48 Mail: info@codan.com www.codan.com

16/03/2015