

Codan 4893 - -

Black, flexible, corrugated, moulded coolant hose for pressureless use.

Please contact Codan for further information.

Type nr. 4893

Application: Coolant / Anti-freeze / Glycol

Standard Length: 1 metres

Working Temperature: -30°C to 110°C

Inside: EPDM Colour: Black

Reinforcement: None

Outside: -Colour: -Standards: -

Inside dia. (mm)	Outside dia. (mm)	Working Pressure BAR	Burst Pressure BAR	Bend Radius (mm)	Weight (g/m)	Product code
25,0	33,0	0	0	20	610	4893025000
32,0	40,0	0	0	30	690	4893032000
38,0	46,0	0	0	50	820	4893038000
45,0	53,0	0	0	75	970	4893045000
51,0	59,0	0	0	75	1.100	4893051000

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. Written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with 150 2230:2002 (Storage

of vulcanised Rubber Products). The individual conditions of an application will affect the lifetime of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber's warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification.

Please contact Codan Rubber for individual product manufacturing tolerances.



© Codan Rubber Danmark A/S Valdemarshaab 1, DK-4600 Køge, Denmark Tel. +45 56 64 64 64 Fax +45 56 64 65 48 Mail: info@codan.com www.codan.com