

Codan 2654 Gas Hose



Codan 2654 - EN ISO 3821 / EN 16436-1

Flexible, smooth, orange hose for liquefied petroleum gas (LPG), propane/butane, to EN ISO 3821 and EN 16436. The hose is primarily for use of assemblies of LPG applications. Further to this, all sizes are DG approved. Please contact Codan for further information.

Type nr. 2654

Application: LPG / Propane / Butane

Standard Length: 50 metres

Working Temperature: -30°C to 80°C

Inside: NBR

Colour: Black

Reinforcement: Ester

Outside: EPDM

Colour: Orange

Standards: EN ISO 3821 / EN 16436-1

Inside dia. (mm)	Outside dia. (mm)	Working Pressure BAR	Burst Pressure BAR	Bend Radius (mm)	Weight (g/m)	Product code
4,0	12,0	30	90	35	120	2654004
6,3	16,3	30	90	45	185	2654006

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. Written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage

of vulcanised Rubber Products). The individual conditions of an application will affect the life time of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber's warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification.

Please contact Codan Rubber for individual product manufacturing tolerances.



© Codan Rubber Danmark A/S Valdemarshaab 1, DK-4600 Køge, Denmark
Tel. +45 56 64 64 64 Fax +45 56 64 65 48 Mail: info@codan.com www.codan.com

16/03/2015