



Applications

For pneumatic tools and general purpose compressed air hose in industrial and other applications.
Suitable for compressed air in all applications, oxygen (ID ≤ 25 mm only), and inert gases for arc welding: argon, nitrogen, and carbon dioxide.
Also for other media (under certain conditions) such as industrial water, aqueous solutions or emulsions for horticultural spraying, white washing, disinfection, acids and alkalis.

Advantages

- n High resistance to abrasion.
- n Good cold flexibility.
- n Wide range of diameters and dimensions.
- n High safety factor.

Technical description

Inner tube: SBR, black, smooth.
Reinforcement: synthetic textile.
Cover: SBR, black, smooth for ID ≤ 25 mm, fabric impression for ID > 25 mm.
Temperature range: -40 °C to +70 °C.
Electrical properties: conductive tube and cover, $R < 10^6 \Omega/m$.

MAXAIR											08/04/2014
ID mm	Wall thickness mm		OD mm		Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Article number	Stock (n) or min. order m
6	3	± 0.4	12	± 0.5	15	50	24	0.13	20	0061321	n
									40	0061322	n
									120	0061323	n
7	3	± 0.5	13	± 0.6	15	50	26	0.15	20	0061324	n
									40	0061325	n
									120	0061326	n
8	3	± 0.5	14	± 0.6	15	50	28	0.16	20	0061327	n
									40	0061328	n
									80	5503090	7040
									120	0061329	n
9	3.5	± 0.5	16	± 0.6	15	50	34	0.22	20	0061330	n
									40	0061331	n
									120	0061332	n
10	3.5	± 0.5	17	± 0.6	15	50	38	0.23	20	0061333	n
									40	0061334	n
									120	0061335	n
13.4	3.6	± 0.6	20.6	± 0.7	15	50	60	0.3	20	5500043	n
									40	5500044	n
									80	5500045	n
16.4	4.6	± 0.7	25.6	± 0.8	15	50	70	0.48	20	5500046	n
									40	5500047	n
									80	5500048	n
19.4	4.6	± 0.7	28.6	± 0.8	15	50	80	0.55	20	5500049	n
									40	5500050	n
									80	5500051	n
25	5	± 1.0	35	± 1.0	15	50	100	0.74	20	5500052	n
									40	5500053	n
									80	5500054	n
30	5.5	± 1.0	41	± 2.0	10	40	300	0.89	20	0200155	n
									40	0200154	n
32	5.5	± 1.0	43	± 2.0	10	40	320	0.94	20	0200158	n
									40	0200157	n
35	6	± 1.0	47	± 2.0	10	40	350	1.13	20	0200161	n
									40	0200160	n
38	6	± 1.0	50	± 2.0	10	40	380	1.21	20	0122111	200
									40	0200163	200
40	6.5	± 1.0	53	± 2.0	10	40	400	1.39	20	0200167	n
									40	0200166	n
45	6.5	± 1.0	58	± 2.0	10	40	450	1.52	20	0200170	200

MAXAIR

08/04/2014

ID mm	Wall thickness mm		OD mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Article number	Stock (n) or min. order m	
								40	0200169	200	
50	7.5	± 1.25	65	± 2.5	10	40	500	1.96	20	0200173	n
								40	0200172	n	
60	7.5	± 1.25	75	± 2.5	10	40	600	2.3	20	0200179	n
								40	0200178	n	
80	7.5	± 1.25	95	± 2.5	10	40	800	3.02	20	0200184	160
								40	0200185	160	
100	7.5	± 1.25	115	± 1.5	10	40	1000	3.59	20	0200189	160
								40	0200190	160	

Branding

ID ≤ 25 mm



ID > 25 mm



and embossed: TRELLEBORG - MAXAIR - ISO 2398:2009 - 1B - L - T - DN - WP 10 BAR - week - year - Made in France



TRELLEBORG

Trelleborg Industrie SAS - ZI La Combaude - Rue de Chantemerle - CS 10725
63050 Clermont-Ferrand cedex 2 France
www.trelleborg.com/industrialhose