


AIRWAP 15

INDUSTRIAL MAINTENANCE
Compressed air applications

TRELLEBORG AIRWAP 15



Applications

Air hose for pneumatic tools and any other compressed air applications.

Also suitable (under certain conditions) for industrial water.

Advantages

- Good resistance to abrasion.
- Good flexibility.
- Good economical solution.

Technical description

Inner tube: SBR, black, smooth.

Reinforcement: synthetic yarns.

Cover: SBR, black, smooth.

Temperature range: - 30 °C to + 70 °C.

AIRWAP 15

19/02/2007

ID	Wall thickness	OD	Working pressure	Bursting pressure	Bending radius	Weight	Length	Article number	Stock (■)		
mm	mm	mm	bar	bar	mm	kg/m	m				
13.4	± 0.6	3.6	20.6	± 0.7	15	45	60	0.30	20	5501210	■
									40	5501179	■
									80	5501211	■
16.4	± 0.7	4.6	25.6	± 0.8	15	45	70	0.48	20	5501212	■
									40	5501180	■
									80	5501213	■
19.4	± 0.7	4.6	28.6	± 0.8	15	45	80	0.55	20	5501214	■
									40	5501181	■
									80	5501215	■
25.0	± 1.0	5.0	35.0	± 1.1	15	45	100	0.74	20	5501216	■
									40	5501182	■
									80	5501217	■

Ink branding

TRELLEBORG AIRWAP 15

WP 15 bar - BP 45 bar

