

# SOLVYKLER

INDUSTRIAL MAINTENANCE  
Solvents/Paints/Lacquer and varnish



## Applications

Pressure service line for ester, ketone, alcohol based paints, and numerous chemicals.

## Advantages

- n Hose cover resistant to splashing of corrosive chemicals.
- n Free from silicone.
- n Hose remains flexible within a wide temperature range.
- n Antistatic tube.

## Technical description

Inner tube: chemical resistant EPDM, black, smooth.

Reinforcement: synthetic textile.

Cover: chemical and weather resistant EPDM, green, smooth.

Temperature range: -30 °C to +100 °C.

Electrical properties: antistatic tube,  $R < 10^6 \Omega/m$ .

## Couplings/Fittings

Special paint hose couplings are recommended.

## SOLVYKLER

08/04/2014

ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Article number	Stock (n) or min. order m		
6	± 0.4	3.3	12.6	± 0.5	20	60	60	0.13	20	0060304	□
									40	0060305	n
									80	0060306	3200
									120	0060307	3240
8	± 0.5	3.5	15	± 0.6	20	60	70	0.16	20	0060308	□
									40	0060309	n
									80	0060310	3280
									120	0060311	3240
9	± 0.5	3.5	16	± 0.6	20	60	85	0.17	20	0060281	□
									40	0060282	n
									80	0060283	3280
									120	0060285	3240
10	± 0.5	4	18	± 0.6	20	60	90	0.22	20	0060312	□
									40	0060313	n
									80	0060314	3280
									120	0060315	3240
13	± 0.6	4	21	± 0.7	20	60	110	0.27	20	0060718	□
									40	0060719	n
									80	0060720	2400
									120	0060721	n
16	± 0.8	4	24	± 1.0	20	60	130	0.32	40	0070140	1200
									80	0070141	1200
20	± 0.8	4.5	29	± 1.0	20	60	150	0.44	20	0070142	□
									40	0070143	n
									80	0070144	n
25	± 1.2	4.5	34	± 1.5	20	60	170	0.54	20	0070145	□
									40	0070146	n
									80	0070147	800

□ Upon availability.

## Branding



Trelleborg Industrie SAS - ZI La Combaude - Rue de Chantemerle - CS 10725  
63050 Clermont-Ferrand cedex 2 France  
[www.trelleborg.com/industrialhose](http://www.trelleborg.com/industrialhose)